

## DVD/CD Flash Copy Tower™ USB Flash Drive/Memory Card Copier and 1:3 DVD/CD Duplicator Aleratec Part # 310108

The DVD/CD Flash Copy Tower™ copies flash memory cards and USB flash drives directly to DVD/CD without a computer. It is also a 1:3 DVD/CD duplicator. The DVD/CD Flash Copy Tower supports disc spanning to four drives so the user can copy full 16GB flash memory cards commonly used by professional photographers and forensics professionals. It copies files and images from volatile flash memory devices to secure and non-erasable DVDs or CDs for safe keeping preserving metatags for date and time. The DVD/CD Flash Copy Tower supports virtually every type of flash memory card and USB flash drive.

### Stand Alone Operation

- Copies USB Flash Drives/Memory Cards to DVD/CD
- Supports Disc Spanning to 4 DVDs/CDs
- Makes 3 DVD/CD Copies at Once
- Video, Photos, Audio, Data
- No Computer Required



Preliminary

see other side →

**Aleratec, Inc.**  
**[www.aleratec.com](http://www.aleratec.com)**

**9851 Owensmouth Ave., Chatsworth, CA 91311**

**Toll Free: (866) 88-ALERATEC (866.882.5372) • Phone: (818) 678-6900 • Fax: (818) 678-0486**



## Technical Specifications

Operation	Stand Alone, no computer required
Function	Memory card copy to DVD/CD disc USB Flash Drive copy to DVD/CD disc 1:3 DVD/CD duplicator Data comparison of copies
USB Flash Drive/ Memory Card to DVD/CD Method	Single session / Multi-session / Disc Spanning (up to 16GB flash memory cards to 4 DVD/CD drives)
USB Flash Drive/ Memory Card File Format	FAT12, FAT16, FAT32
Compatibility	
MS Slot:	MS, MS Duo, MS Pro, MS Pro Duo, MS Micro (M2)*
CF Slot:	CF I, CF II, Micro Drive
SD/MMC Slot:	SD, SDHC, miniSD*, miniSDHC*, microSD*, microSDHC*, WiFi SD, MMC, RS-MMC*, MMCplus*, MMCmicro*
USB Flash Drives:	USB1.1/2.0 USB flash drives
DVDs/CDs:	DVD±R, DVD±RW, dual layer DVD±R, 3-inch mini CD-R, standard CD-R/RW
Max Writing Speed	20X DVD±R, 8x dual layer DVD±R, 8x DVD+RW, 6x DVD-RW, 48x CD-R, 32x CD-RW
Display	2 x 16 backlighted LCD
Control Buttons	Forward, Backward, Escape, and OK
Power	Switchable 115V / 230V
Humidity	Working: 20% ~ 80% ; Storage: 5% ~ 95%
Environment	Working : 41° to 104° F
Dimensions (inches)	15 x 7.5 x 10.5 (LxWxH)
Weight	22 lbs

see other side →

Aleratec, Inc.

www.aleratec.com

9851 Owensmouth Ave., Chatsworth, CA 91311

Toll Free: (866) 88-ALERATEC (866.882.5372) • Phone: (818) 678-6900 • Fax: (818) 678-0486