

Rimage Producer™ IV Specifications

This document provides product specification information for the Rimage Producer IV. These products are part of the Rimage Producer series and include the 6200, 6200N, 7200N, and 8200N. For more information on how to operate, identify the parts of, and configure the printing preferences for these products, refer to the *Rimage Producer IV User Guide*.

Note: Printer specifications as well as manuals referred to in this document are available at www.rimage.com/support. From the **Support** menu select: **Product Series > Product Name > User Manuals** tab.

		Producer IV			
		6200	6200N	7200N	8200N
Physical size	Height	28.0 in (71.1 cm)	28.0 in (71.1 cm)	30.5 in (77.5 cm)	33.5 in (85.1 cm)
	Width	17.3 in (43.8 cm)	17.3 in (43.8 cm)	17.3 in (43.8 cm)	17.3 in (43.8 cm)
	Depth*	24.0 in (61.0 cm)	24.0 in (61.0 cm)	24.0 in (61.0 cm)	24.0 in (61.0 cm)
	Weight	76.0 lb (34.5 kg)	98.5 lb (44.7 kg)	102.5 lb (46.5 kg)	114.5 lb (52.0 kg)
	Weight with Everest	121.0 lb (55.0 kg)	143.5 lb (65.1 kg)	147.5 lb (67.0 kg)	159.5 lb (72.3 kg)
	Weight with Prism III	96.0 lb (43.5 kg)	118.5 lb (53.8 kg)	122.5 lb (55.6 kg)	134.5 lb (61.0 kg)
	* Leave an additional 3.5 in (9 cm) for cabling.				
Number of recorders	1	1	2	4	
Standard System	6200 autoloader, Everest or Prism printer, Rimage Software Suite – Network, and external PC.				
	6200N, 7200N, or 8200N autoloader, Everest or Prism printer, and Rimage Software Suite – Network.				
Software requirements	Rimage Software Suite is installed on the external (non-embedded) PC. The required Rimage Software Suite is installed on the embedded PC.				

		Producer IV			
		6200	6200N	7200N	8200N
PC Specifications		<p>Note: The Rimage system software runs on an external or embedded PC. Macintosh computers can send disc publishing jobs to Rimage Producer systems by using Rimage DiscFlow software for Macs.</p> <p>Important! If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.</p>			
		Minimum PC Requirements (6200)*		Embedded PC Specifications	
	Supported operating systems	<ul style="list-style-type: none"> Windows 7 Professional and Ultimate (32-/64-bit) Windows 7 Enterprise (64-bit) Windows XP Professional SP3 (32-bit) Windows Vista Business, Enterprise, and Ultimate editions with SP2 (32-bit) Windows Server 2008 R2 (64-bit) 		<ul style="list-style-type: none"> Windows 7 Ultimate SP1 (64-bit) Windows Server 2008 R2 Standard 64-bit (Optional) 	
	Processor	Minimum: Celeron, 2.0 GHz Recommended: Core 2 Duo, E4300		Intel Core i5	
	RAM/Memory	2 GB (4 GB recommended)		8 GB	
	I/O	Minimum: Use an integrated high-speed USB 2.0 port Recommended: Use an integrated high-speed USB 3.0 port		USB 2.0 Ports: <ul style="list-style-type: none"> 1 Located on the front of the system 4 Located on the back of the system USB 3.0 Ports: <ul style="list-style-type: none"> 2 Located on the back of the system 	
	Hard Disc Drive	Minimum: 60 GB of free space Recommended: Two 250GB, 7,200 RPM Enterprise Class Serial ATA hard drives configured in RAID 0: <ul style="list-style-type: none"> Partition one is used to house the operating system. Partition two is used for the Rimage System Folder 		7200N/8200N: Four hard disk drives (500 GB each; 7,200 RPM SATA) 6200N: Three hard disk drives (500 GB each; 7,200 RPM SATA)	
	RAID	See HDD specification above		Volume 1: RAID 5 – 80 GB (Boot) Volume 2: RAID 0 – 1.7 TB (Data)	
	Network	N/A		Intel Pro 10/100/1000 Mbps	
	Removable Storage	CD/DVD-ROM		N/A	
Graphics	Minimum: 1024 x 768, 16-bit color Recommended: 1024 x 768, 32-bit high color		N/A		

*These optimum PC specifications are recommended if you are using the Rimage Producer 6200 to record CD/DVD/BDs. Throughput is based on this system configuration. For optimum performance, use a PC with these specifications.

	Producer IV									
	6200	6200N	7200N	8200N						
Input bin capacity	Rotating four-bin carousel capable of holding 100 discs per bin. Note: You can configure the Producer IV to have 4 input bins if you configure the external output bin as the only output bin.									
Output bin capacity	300 discs before operator intervention is required when the carousel is used as the output bin. 400 discs before operator intervention is required when the external output bin is used as an output bin.									
Networking ability	To submit orders from a networked PC, refer to the <i>Rimage Advanced Setup (Networking) Guide</i> .									
Power	100 – 240 VAC, 60/50 Hz, 4.7 – 3.7 Amp, 500 watt maximum									
Media requirements	Refer to your printer user guide for the correct media requirements. Rimage Media Kits™ are designed for optimum recording and print performance.									
Ribbon requirements	Refer to your printer user guide for the correct printer ribbons. Rimage Media Kits include the required print ribbons.									
Label design requirements	Refer to your printer user guide for label design requirements.									
Temperature and humidity	<table border="0"> <tr> <td style="padding-right: 10px;">Operating temperature</td> <td>41° to 95° F (5° to 35° C)</td> </tr> <tr> <td style="padding-right: 10px;">Humidity</td> <td>20% to 80% RH non-condensing</td> </tr> <tr> <td style="padding-right: 10px;">Storage temperature</td> <td>5° to 95° F (-15° to 35° C)</td> </tr> </table>				Operating temperature	41° to 95° F (5° to 35° C)	Humidity	20% to 80% RH non-condensing	Storage temperature	5° to 95° F (-15° to 35° C)
Operating temperature	41° to 95° F (5° to 35° C)									
Humidity	20% to 80% RH non-condensing									
Storage temperature	5° to 95° F (-15° to 35° C)									